



Spec Sheet

Product / Variant	LiBa®Safe XLg <i>Inner packaging for lithium batteries</i>
Item number	110014
Outer dimensions L x W x H in mm (approx.)	2450 x 1250 x 900 mm
Inner dimensions L x W x H in mm (approx.)	2650 x 1400 x 980 mm
Net weight in kg (ca.)	436 kg
Construction	Steel tray & lid with multi-layer special textile / LiBa®Vent system
Manufacturer	GelKoh GmbH
Extinguishing system	includes LiBa®Sol
Trigger	Passively at ca. 180 °C
Features	LiBa®Vent System - Gas-permeable with particle barrier, HF-absorbing, construction and inner coating according to DIN 4102-I / A1, non-combustible
Accessories	Lifting straps, special fasteners, forklift profiles, airline rail for load securing
Area of application	Inner packaging according to ADR, operating temperature -40 to 100 degrees Celsius Quarantine zone / storage location For outdoor storage, protect from weather. Cover or shelter it or order a rain cover as an accessory!
Gasmanagement	In accordance with ADR, HF-reducing

Der Hersteller bescheinigt hiermit die Eigenüberwachung des Erzeugnisses, sowie das durch die BAM anerkannte QS System
Die Herstellung erfolgte zeichnungs- und normgerecht. (Je nach Ausführung Abbildung ähnlich / Änderungen vorbehalten!)