


Product Datasheet model uvex megasonic 9320 265**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

| | |
|--------------------------------|--|
| Product characteristics | <ul style="list-style-type: none">• revolutionary goggles with exceptional field of vision• unique frameless lens design• OTG compatible with frame recess for side arms• soft, adaptive face seal for incredible comfort and fit• 30-mm-wide headband for a superior, no pressure fit• easily interchangeable headband and lens• highly compatible with other items of PPE• uvex's proven supravision coating technology |
| Technical details | |
| Frame | |
| Material | PVC |
| Colour | anthracite |

| | |
|---|---|
| Headband | |
| Material | textile headband |
| Colour | blue |
| Marking | |
| Manufacturer's ID code | W |
| Applicable EN norm | 166 |
| Field of use | 3 (drops and splashes of liquid) 4 (large dust particles) |
| Impact resistance | B (120 m/s) |
| Resistance to high speed particles at extremes of temp. | T |
| Conformity symbol | CE |
| Lens | |
| Material | PC |
| Thickness | 2,40 mm |
| Coating | uvex supravision excellence |
| Colour | clear |
| UV protection | UV 400 |
| Marking | |
| Filter | 2C-1,2 (DIN EN 170) |
| Manufacturer's ID code | W |
| Optical class | 1 |
| Impact resistance | B (120 m/s) |
| Resistance to high speed particles at extremes of temp. | T |
| Surface resistance to fine particles | K |
| Antifog | N |
| Conformity symbol | CE |
| Factory symbol |  |

Miscellaneous

| | |
|--------------|---|
| Weight | 107 g |
| Packing | 4 spectacles per box 64 spectacles per cardboard box |
| Standards | DIN EN 166 + DIN EN 170 |
| PPE Category | Category II |